



**Ultrasound
Solutions**

COMMONSense Range
4-20mA & 0-10V Heterodyne Sensors



COMMONSense range includes standalone sensors with both 4-20mA and 0-10V output, per each output, 3 sensors are available: Contact or structure, Airborne open, Airborne enclosed

COMMONSense Range is a Standalone, Permanent Mount, Ultrasound Sensor designed to integrate with standard industrial measurement systems. COMMONSense delivers precise, repeatable data about the health of your assets and electrical systems also in the most challenging environment.

Its resonant piezo element is optimized for ultrasound driven lubrication, mechanical fault detection, and monitoring the health of valves, steam, hydraulic systems and electrical defects.

COMMONSense sensors can be used in multiple applications:

- Contact/structure (IP65) for bearings lubrication, valves, steam traps, hydraulics systems and rotating assets inspections, even the slowest ones.
- Airborne open (IP40) and enclosed (IP65) for inspection of electrical systems.

Ultrasound is a true measure of the FITness of your facility. Most assets produce FRICTION, IMPACTING, and TURBULENCE as defect indicators. COMMONSense hears these phenomena at their inception and delivers an analog signal response to your connected measurement system.


With an output range from 4-20mA or from 0-10V, COMMONSense mounts permanently to any asset to provide continuous condition monitoring data.

Avoid unplanned downtime and put the safety of your plant and colleagues first.

SPECIFICATIONS

4-20mA Contact Sensor IP65 / 0-10V Contact Sensor IP65:


- Static or dynamic output;
- Onboard amplification stages;
- Non-volatile memory (used to save configuration and recover sensor state/mode upon power outage);
- Hardware calibration;
- Unique ID;
- Digital I/O communication for simple use;
- Serial communication for advanced use.



Technical data:			
Weight	126 Gram / 4.44 oz	Gain range	0 [dB] to 60 [dB]
IP rating	65	Gain step	12 [dB]
Power supply	10 [V] to 30 [V]	Connector size	M8 - 4 pin
Operating t°	-20 [°C] to +85 [°C] / -4 [°F] to +185 [°F]	Heterodyne frequency	38.5 [kHz] +/- 10%
Pinout voltage	GROUND to VDD	Bandwidth	[0.25 - 4] [kHz]
Resonant frequency	37 [kHz] +/- 1 [kHz]	RMS time period	1 [s]

4-20mA Airborne Sensor IP65 / 0-10V Airborne Sensor IP65:


- Static or dynamic output;
- Onboard amplification stages;
- Non-volatile memory (used to save configuration and recover sensor state/mode upon power outage);
- Hardware calibration;
- Unique ID;
- Digital I/O communication for simple use;
- Serial communication for advanced use.



Technical data:			
Weight	82 Gram / 2.9 Oz	Gain range	0 [dB] to 60 [dB]
IP rating	65	Gain step	12 [dB]
Power supply	10 [V] to 30 [V]	Connector size	M8 - 4 pin
Operating t°	-20 [°C] to +70 [°C] / -4 [°F] to +158 [°F]	Heterodyne frequency	38.5 [kHz] +/- 10%
Pinout voltage	GROUND to VDD	Bandwidth	[0.25 - 4] [kHz]
Resonant frequency	40 [kHz] +/- 1 [kHz]	RMS time period	1 [s]

4-20mA Airborne Open Sensor IP40 / 0-10V Airborne Open Sensor IP40:

- Static or dynamic output;
- Onboard amplification stages;
- Non-volatile memory (used to save configuration and recover sensor state/mode upon power outage);
- Hardware calibration;
- Unique ID;
- Digital I/O communication for simple use;
- Serial communication for advanced use.



Technical data:			
Weight	82 Gram / 2.9 Oz	Gain range	0 [dB] to 60 [dB]
IP rating	40	Gain step	12 [dB]
Power supply	10 [V] to 30 [V]	Connector size	M8 - 4 pin
Operating t°	-20 [°C] to +70 [°C] / -4 [°F] to +158 [°F]	Heterodyne frequency	38.5 [kHz] +/- 10%
Pinout voltage	GROUND to VDD	Bandwidth	[0.25 - 4] [kHz]
Resonant frequency	40 [kHz] +/- 1 [kHz]	RMS time period	1 [s]

Accessories offered by SDT:

Cables with straight M8 connector

FU.RSC.CABL.01.015-1	Sensor-/actor cable m8 4pf <> free end 1.5m/4.9ft - straight shielded
FU.RSC.CABL.01.030-1	Sensor-/actor cable m8 4pf <> free end 3.0m/9.8ft - straight shielded
FU.RSC.CABL.01.050-1	Sensor-/actor cable m8 4pf <> free end 5.0m/16.4ft - straight shielded
FU.RSC.CABL.01.100-1	Sensor-/actor cable m8 4pf <> free end 10.0m/32.8ft - straight shielded

Cables with 90° M8 connector

FU.RSC.CABL.02.015-1	Sensor-/actor cable m8 4pf <> free end 1.5m/4.9ft - 90° shielded
FU.RSC.CABL.02.030-1	Sensor-/actor cable m8 4pf <> free end 3.0m/9.8ft - 90° shielded
FU.RSC.CABL.02.050-1	Sensor-/actor cable m8 4pf <> free end 5.0m/16.4ft - 90° shielded
FU.RSC.CABL.02.100-1	Sensor-/actor cable m8 4pf <> free end 10.0m/32.8ft - 90° shielded

OUR MISSION:

SDT provides ultrasound solutions that help our customers gain a better understanding about the health of their assets. We help them predict failures, control tightness, optimize energy costs, and improve product quality while contributing to the overall reliability of their organization.



SDT International s.a./n.v.

Bd de l'Humanité, 415
B-1190 Brussels (Belgium)
Tel: +32(0)2-332 32 25
Email: info@sdtultrasound.com

SDT North America

7677 County Road 2
Cobourg ON K9A 0X4 (Canada)
Phone: 1-800-667-5325 / 1-905-377-1313
Email: hearmore@sdtultrasound.com



Edificio Antalia, Albasanz 16, 28037 Madrid
915 679 700 | preditec.com | info@preditec.com

MADRID - BARCELONA - ZARAGOZA - LISBON - DALLAS - MIAMI - LOS ANGELES - LIMA